

Handgun reloading data

Cartridge

Cartridge	9 mm Browning court / .380 Auto
Test barrel	82 mm (3"), 1 in 10" twist
Primers	Small Pistol
Cases	X-Treme Bullets, trim-to length 17,15 mm (0.680")



VIHTAVUORI

Bullet specifications

Your search returned **22** different loads:

Bullet				Powder	Load				
g				mm		g		m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity		
					start	max	start	max	
5,8	Sig Sauer	V-Crown JHP	25,0	N310	0,16	0,18	277	293	
5,8	Sig Sauer	V-Crown JHP	25,0	N320	0,21	0,23	270	308	
5,9	Hornady	HP-XTP	24,9	N310	0,14	0,17	246	290	
5,9	Hornady	HP-XTP	24,9	N320	0,20	0,23	266	319	
5,9	Hornady	HP-XTP	24,9	N32C	0,22	0,23	270	268	
6,2	Speer	TMJ	25,0	N310	0,15	0,17	249	282	
6,2	Speer	TMJ	25,0	N320	0,21	0,23	265	309	
6,2	Speer	TMJ	25,0	N330	0,24	0,27	265	315	
6,5	Berry's	HBRN, Copper Plated	25,0	N310	0,14	0,16	218	251	
6,5	Berry's	HBRN, Copper Plated	25,0	N320	0,19	0,22	250	298	
6,5	Berry's	HBRN, Copper Plated	25,0	N330	0,22	0,25	257	295	
6,5	Berry's	Hybrid Hollow Point, Copper Plated	25,0	N310	0,14	0,17	209	257	
6,5	Berry's	Hybrid Hollow Point, Copper Plated	25,0	N320	0,19	0,22	241	292	
6,5	Berry's	Hybrid Hollow Point, Copper Plated	25,0	N330	0,23	0,26	254	296	
6,5	H&N	HP HS	25,0	N310	0,13	0,15	232	267	
6,5	H&N	HP HS	25,0	N320	0,18	0,21	253	300	
6,5	Hornady	FMJ	25,0	N310	0,13	0,16	232	270	
6,5	Hornady	FMJ	25,0	N320	0,18	0,21	243	296	
6,5	Hornady	FMJ	25,0	N330	0,21	0,25	243	306	
6,5	X-Treme Bullets	RNFP	24,3	N310	0,14	0,17	247	273	
6,5	X-Treme Bullets	RNFP	24,3	N320	0,18	0,22	248	297	
6,5	X-Treme Bullets	RNFP	24,3	N32C	0,18	0,22	239	280	